



**BATTERY TENDER ≤  
WATERPROOF 800  
INTERNATIONAL  
12 VOLT 800 mAmp**

**WATERPROOF**

**Single Output 12 Volt Battery Charger**

Note: This unit is operated and performs exactly like the Battery Tender ≤ Junior single output unit. The only difference is that the DC output current is higher at 800 mA compared to 750 mA, and the AC input is universal.

- **SUPER SMART TECHNOLOGY**
- **SPARK PROOF**
- **SHORT CIRCUIT PROTECTED**
- **REVERSE POLARITY PROTECTED**
- **WATERPROOF**
- **3-Step Charging** (Qualification, Bulk, & Float Maintenance)
- **WEIGHS ONLY 0.5kg** (0.55kg With Power Cords)
- **3 YEAR WARRANTY**

TECHNICAL SPECIFICATION SUMMARY		
Input Voltage & Frequency		100 to 240 VAC, 50/60 Hz
<b>DC OUTPUT</b>		
Output Current	Bulk Charge	800 mA DC Constant
Output Voltage	Absorption Charge Peak	14.4 VDC Maximum
	Maintenance Charge	13.2 VDC Constant
Operating Temperature (100 to 200 VAC)		-20 °C to +50 °C
<b>DIMENSIONS &amp; WEIGHT</b>		
Charger Case Dimensions (Without Cords)	4.2 in (107 mm) L x 2.75 in (70 mm) W x 1.4 in (36 mm) H Allow an additional 1 in (25.4 mm) on each end of the length dimension for safe bend of AC and DC power cord strain relief.	
Shipping Box	Approx: 10.75 in (273 mm) L x 10.75 in (273 mm) W x 3.75 in (95 mm) H	
Typical shipping Weight	<b>WITH:</b> Alligator clips & fused Ring terminal cables in Clamshell packaging	1.14 kg

